



QUALITY CHECK VALVES

SINCE 1983

2804 W 40th St
Tulsa, OK 74107
t. (800) 346-6310
f. (918) 445-7717

www.youngenergyproducts.com

TABLE OF CONTENTS

THREADED END CHECK VALVES

BRONZE	01
ALUMINUM BRONZE	02
CAST IRON	03
DUCTILE IRON	04
STEEL	05
STAINLESS STEEL	06

GROOVED END CHECK VALVES	07
--------------------------	----

FLANGED END CHECK VALVES	08
--------------------------	----

WAFFER CHECK VALVES	09
---------------------	----

PLUG VALVE	10
------------	----

BALL CHECK VALVES	11
-------------------	----

INLINE CHEMICAL CHECK VALVES	
GRADUATED DIAL COCK VALVE	12

BALL VALVES	13-14
-------------	-------

TANK VALVES	15
-------------	----

TERMS AND CONDITIONS	16
----------------------	----

WARRANTY	17
----------	----



THREADED END CHECK VALVES

BRONZE



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	300	3 1/2"	2	CVB-1-300
	500	4 1/8"	5	CVB-1-500
2"	300	5 1/8"	6	CVB-2-300
	500	5 1/8"	8	CVB-2-500
2.5"	300	8 3/16"	20	CVB-2.5-300
3"	300	8 3/16"	18	CVB-3-300
4"	300	9 1/4"	32	CVB-4-300



2804 W 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717
www.youngenergyproducts.com

THREADED END CHECK VALVES

ALUMINUM BRONZE



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	275	4 3/8"	4	CVAB-1-275
	720	4 3/8"	4	CVAB-1-720
	960	4 3/8"	4	CVAB-1-960
	1440	4 3/8"	4	CVAB-1-1440
	2160	4 3/8"	4	CVAB-1-2160
2"	1000	5 1/8"	7	CVAB-2-1000
2"	275	7 1/4"	16	CVAB-2-275
	720	7 1/4"	16	CVAB-2-720
	960	7 1/4"	16	CVAB-2-960
	1440	7 1/4"	16	CVAB-2-1440
	2160	7 1/4"	16	CVAB-2-2160
2 1/2"	275	8 3/16"	24	CVAB-2.5-275
	720	8 3/16"	24	CVAB-2.5-720
	960	8 3/16"	24	CVAB-2.5-960
	1440	8 3/16"	24	CVAB-2.5-1440
	2160	8 3/16"	24	CVAB-2.5-2160
3"	275	8 3/16"	23	CVAB-3-275
	720	8 3/16"	23	CVAB-3-720
	960	8 3/16"	23	CVAB-3-960
	1440	8 3/16"	23	CVAB-3-1440
	2160	8 3/16"	23	CVAB-3-2160
4"	275	9 1/4"	27	CVAB-4-275
	720	9 1/4"	27	CVAB-4-720
	960	9 1/4"	27	CVAB-4-960
	1440	9 1/4"	27	CVAB-4-1440
	2160	9 1/4"	27	CVAB-4-2160



2804 W 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717
www.youngenergyproducts.com

THREADED END CHECK VALVES

IRON



CAST IRON IBBM

VALVE SIZE (IN)	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
2"	300	7 1/4"	14	CVC-2-300-IBBM
	600	7 1/4"	14	CVC-2-600-IBBM
2 1/2"	300	8 3/16"	20	CVC-2.5-300-IBBM
	600	8 3/16"	20	CVC-2.5-600-IBBM
3"	300	8 3/16"	23	CVC-3-300-IBBM
	600	8 3/16"	23	CVC-3-600-IBBM
4"	300	9 7/8"	29	CVC-4-300-IBBM
	600	9 7/8"	29	CVC-4-600-IBBM

THREADED END CHECK VALVES

DUCTILE NACE



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	300	4 1/8"	4	CVD-1-300
	600	4 1/8"	4	CVD-1-600
	1000	4 1/8"	4	CVD-1-1000
	1500	4 1/8"	4	CVD-1-1500
	2000	4 1/8"	4	CVD-1-2000
2" Short Body	300	6"	10	CVD-2-300
	600	6"	10	CVD-2-600
	1000	6"	10	CVD-2-1000
	1500	6"	10	CVD-2-1500
	2000	6"	10	CVD-2-2000
2" Long Body	300	7 1/4"	11	CVD-2-300-L
	600	7 1/4"	11	CVD-2-600-L
	1000	7 1/4"	11	CVD-2-1000-L
	1500	7 1/4"	11	CVD-2-1500-L
	2000	7 1/4"	11	CVD-2-2000-L
2.5"	300	8 3/16"	20	CVD-2.5-300
	600	8 3/16"	20	CVD-2.5-600
	1000	8 3/16"	20	CVD- 2.5-1000
	1500	8 3/16"	20	CVD-2.5-1500
	2000	8 3/16"	20	CVD-2.5-2000
3"	300	8 3/16"	25	CVD-3-300
	600	8 3/16"	25	CVD-3-600
	1000	8 3/16"	25	CVD-3-1000
	1500	8 3/16"	25	CVD-3-1500
	2000	8 3/16"	25	CVD-3-2000
4"	300	9 7/8"	28	CVD-4-300
	600	9 7/8"	28	CVD-4-600
	1000	9 7/8"	28	CVD-4-1000
	1500	9 7/8"	28	CVD-4-1500



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

THREADED END CHECK VALVES

STEEL



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	275	4 1/8"	4	CVS-1-275
	720	4 1/8"	4	CVS-1-720
	1440	4 1/8"	4	CVS-1-1440
	2160	4 1/8"	4	CVS-1-2160
	3000	4 1/8"	4	CVS-1-3000
2"	275	7 1/4"	18	CVS-2-275
	720	7 1/4"	18	CVS-2-720
	1440	7 1/4"	18	CVS-2-1440
	2160	7 1/4"	18	CVS-2-2160
	3000	7 1/4"	18	CVS-2-3000
2.5"	275	8 3/16"	21	CVS-2.5-275
	720	8 3/16"	21	CVS-2.5-720
	1440	8 3/16"	21	CVS-2.5-1440
	2160	8 3/16"	21	CVS-2.5-2160
	3000	8 3/16"	21	CVS-2.5-3000
3"	275	8 3/16"	26	CVS-3-275
	720	8 3/16"	26	CVS-3-720
	1440	8 3/16"	26	CVS-3-1440
	2160	8 3/16"	26	CVS-3-2160
	3000	8 3/16"	26	CVS-3-3000
4"	275	9 7/8"	30	CVS-4-275
	720	9 7/8"	30	CVS-4-720
	1440	9 7/8"	30	CVS-4-1440



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

THREADED END CHECK VALVES

STAINLESS STEEL



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	275	4 1/8"	5	CVSS-1-275
	720	4 1/8"	5	CVSS-1-720
	1440	4 1/8"	5	CVSS-1-1440
	2160	4 1/8"	5	CVSS-1-2160
	3000	4 1/8"	5	CVSS-1-3000
2"	275	7 1/4"	18	CVSS-2-275
	720	7 1/4"	18	CVSS-2-720
	1440	7 1/4"	18	CVSS-2-1440
	2160	7 1/4"	18	CVSS-2-2160
	3000	7 1/4"	18	CVSS-2-3000
3"	275	8 5/16"	26	CVSS-3-275
	720	8 5/16"	26	CVSS-3-720
	1440	8 5/16"	26	CVSS-3-1440
	2160	8 5/16"	26	CVSS-3-2160
	3000	8 5/16"	26	CVSS-3-3000



2804 W 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717
www.youngenergyproducts.com

GROOVED END CHECK VALVES



BRONZE

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
2"	300	6 1/32"	6	GCVB-2-300
3"	300	7 5/8"	17	GCVB-3-300
4"	300	10 1/8"	38	GCVB-4-300



DUCTILE IRON

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	DUCTILE ORDER #
2"	300	9"	19	GCVD-2-300
	600	9"	19	GCVD-2-600
	1000	9"	19	GCVD-2-1000
3"	300	10 3/4"	24	GCVD-3-300
	600	10 3/4"	24	GCVD-3-600
	1000	10 3/4"	24	GCVD-3-1000
4"	300	12 1/2"	40	GCVD-4-300
	600	12 1/2"	40	GCVD-4-600
	1000	12 1/2"	40	GCVD-4-1000



ALUMINUM BRONZE

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
2"	2160	9"	19	GCVAB-2-2160



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

FLANGED END CHECK VALVES

STEEL BOLTED TOP



VALVE SIZE	ANSI CLASS	WORKING PRESSURE (PSI)	END-TO-END LENGTH (RF) (IN)	END-TO-END LENGTH (RTJ) (IN)	WEIGHT (LBS)	ORDER #
2"	150	275	8"	—	33	FCVS-2-150
	300	720	10 1/2"	11 1/8"	50	FCVS-2-300
	600	1440	11 1/2"	11 5/8"	55	FCVS-2-600
	900	2160	14 1/2"	14 5/8"	79	FCVS-2-900
	1500	3600	14 1/2"	14 5/8"	105	FCVS-2-1500
3"	150	275	9 1/2"	—	45	FCVS-3-150
	300	720	12 1/2"	13 1/8"	96	FCVS-3-300
	600	1440	14"	14 1/8"	101	FCVS-3-600
	900	2160	15"	15 1/8"	119	FCVS-3-900
	1500	3600	18 1/2"	18 5/8"	149	FCVS-3-1500
4"	150	275	11 1/2"	—	70	FCVS-4-150
	300	720	14"	14 5/8"	138	FCVS-4-300
	600	1440	17"	17 1/8"	175	FCVS-4-600
	1500	3600	21 1/2"	21 5/8"	225	FCVS-4-1500
6"	150	275	14"	—	155	FCVS-6-150
	300	720	17 1/2"	18 1/8"	185	FCVS-6-300
	600	1440	22"	22 1/8"	335	FCVS-6-600
8"	150	275	19 1/2"	—	280	FCVS-8-150
	300	720	21"	21 5/8"	360	FCVS-8-300
	600	1440	26"	26 1/8"	525	FCVS-8-600
10"	150	275	24 1/2"	—	390	FCVS-10-150
	300	720	24 1/2"	25 1/8"	460	FCVS-10-300
	600	1440	31"	31 1/8"	925	FCVS-10-600
12"	150	275	27 1/2"	—	650	FCVS-12-150
	300	720	28"	28 5/8"	900	FCVS-12-300
	600	1440	33"	33 1/8"	1355	FCVS-12-600

WAFER CHECK VALVES

STEEL



VALVE SIZE*	ANSI CLASS	WORKING PRESSURE (PSI)	OD (IN)	ID (IN)	BODY THICKNESS (IN)	WEIGHT (LBS)	ORDER #**
2"	150	275	4 1/8"	1"	3/4"	3	WCS-2-150
	300	720	4 3/8"	1"	3/4"	3.5	WCS-2-300
	600	1440	4 3/8"	1"	3/4"	4.5	WCS-2-600
	900	2160	5 5/8"	1"	3/4"	5	WCS-2-900
	1500	3600	5 5/8"	1"	3/4"	6	WCS-2-1500
3"	150	275	5 3/8"	1 3/4"	3/4"	5	WCS-3-150
	300	720	5 7/8"	1 3/4"	3/4"	6	WCS-3-300
	600	1440	5 7/8"	1 3/4"	3/4"	7.5	WCS-3-600
	900	2160	6 5/8"	1 3/4"	3/4"	9	WCS-3-900
	1500	3600	6 7/8"	1 3/4"	7/8"	12	WCS-3-1500
4"	150	275	6 7/8"	2 5/8"	3/4"	6.5	WCS-4-150
	300	720	7 1/8"	2 5/8"	3/4"	8	WCS-4-300
	600	1440	7 5/8"	2 5/8"	7/8"	11	WCS-4-600
	900	2160	8 1/8"	2 5/8"	7/8"	12.5	WCS-4-900
	1500	3600	8 1/4"	2 5/8"	1 1/4"	18	WCS-4-1500
6"	150	275	8 3/4"	4 3/8"	3/4"	13	WCS-6-150
	300	720	9 7/8"	4 3/8"	7/8"	15	WCS-6-300
	600	1440	10 1/2"	4"	1 1/8"	22	WCS-6-600
	900	2160	11 1/8"	4"	1 3/8"	27	WCS-6-900
8"	150	275	11"	6"	1 1/8"	26	WCS-8-150
	300	720	12 1/8"	6"	1 1/8"	30	WCS-8-300
	600	1440	12 5/8"	5"	1 1/2"	40	WCS-8-600
10"	150	275	13 3/8"	7 3/4"	1 1/8"	37	WCS-10-150
	300	720	14 1/4"	7 3/4"	1 1/2"	54	WCS-10-300
	600	1440	15 3/4"	6 7/8"	2 1/4"	110	WCS-10-600
12"	150	275	16 1/8"	9 1/2"	1 1/2"	71	WCS-12-150
	300	720	16 5/8"	9 1/2"	2"	97	WCS-12-300
	600	1440	18"	8 1/2"	2 3/8"	145	WCS-12-600

*Sizes above 12" available on special request. Contact the factory for pricing and availability.

**For Stainless Steel, add "SS" to the end of the Order Number.



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

WAFER CHECK VALVES

STAINLESS STEEL



VALVE SIZE*	ANSI CLASS	WORKING PRESSURE (PSI)	OD (IN)	ID (IN)	BODY THICKNESS (IN)	WEIGHT (LBS)	ORDER #**
2"	150	275	4 1/8"	1"	3/4"	3	WCSS-2-150
	300	720	4 3/8"	1"	3/4"	3.5	WCSS-2-300
	600	1440	4 3/8"	1"	3/4"	4.5	WCS-2-600
	900	2160	5 5/8"	1"	3/4"	5	WCS-2-900
	1500	3600	5 5/8"	1"	3/4"	6	WCS-2-1500
3"	150	275	5 3/8"	1 3/4"	3/4"	5	WCS-3-150
	300	720	5 7/8"	1 3/4"	3/4"	6	WCS-3-300
	600	1440	5 7/8"	1 3/4"	3/4"	7.5	WCS-3-600
	900	2160	6 5/8"	1 3/4"	3/4"	9	WCS-3-900
	1500	3600	6 7/8"	1 3/4"	7/8"	12	WCS-3-1500
4"	150	275	6 7/8"	2 5/8"	3/4"	6.5	WCS-4-150
	300	720	7 1/8"	2 5/8"	3/4"	8	WCS-4-300
	600	1440	7 5/8"	2 5/8"	7/8"	11	WCS-4-600
	900	2160	8 1/8"	2 5/8"	7/8"	12.5	WCS-4-900
	1500	3600	8 1/4"	2 5/8"	1 1/4"	18	WCS-4-1500
6"	150	275	8 3/4"	4 3/8"	3/4"	13	WCS-6-150
	300	720	9 7/8"	4 3/8"	7/8"	15	WCS-6-300
	600	1440	10 1/2"	4"	1 1/8"	22	WCS-6-600
	900	2160	11 1/8"	4"	1 3/8"	27	WCS-6-900
8"	150	275	11"	6"	1 1/8"	26	WCS-8-150
	300	720	12 1/8"	6"	1 1/8"	30	WCS-8-300
	600	1440	12 5/8"	5"	1 1/2"	40	WCS-8-600
10"	150	275	13 3/8"	7 3/4"	1 1/8"	37	WCS-10-150
	300	720	14 1/4"	7 3/4"	1 1/2"	54	WCS-10-300
	600	1440	15 3/4"	6 7/8"	2 1/4"	110	WCS-10-600
12"	150	275	16 1/8"	9 1/2"	1 1/2"	71	WCS-12-150
	300	720	16 5/8"	9 1/2"	2"	97	WCS-12-300
	600	1440	18"	8 1/2"	2 3/8"	145	WCS-12-600

*Sizes above 12" available on special request. Contact the factory for pricing and availability.

**For Stainless Steel, add "SS" to the end of the Order Number.



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

PLUG VALVE



VALVE SIZE	WORKING PRESSURE (PSI @ 100° F)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	WRENCH ORDER #	ORDER #
2"	175	6.00	14	PVD-2-HDL	PVD-2-175
3"	175	7.83	38	PVD-3-HDL	PVD-3-175
4"	175	9.25	48	PVD-4-HDL	PVD-4-175

*Handles are sold separately
Lock key and chain available for each size*

BILL OF MATERIALS

PART	MATERIAL	NUMBER
Body/Cap/ Stem	Class 30 Grey Iron	1
Button Head	Zinc Plated Steel	1
Bolts	Zinc Plated Steel	2
Seal	Grease	



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717
www.youngenergyproducts.com

BALL CHECK VALVES



ALUMINUM BRONZE

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	2000	4 1/2"	5	BCVAB-1-2000
2"	2160	6 3/8"	15	BCVAB-2-2160



DUCTILE IRON

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	1000	4 1/2"	5	BCVD-1-1000
	1500	4 1/2"	5	BCVD-1-1500
	2000	4 1/2"	5	BCVD-1-2000
2"	1000	6 3/8"	15	BCVD-2-1000
	1500	6 3/8"	15	BCVD-2-1500
	2000	6 3/8"	15	BCVD-2-2000



STEEL

VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	2160	4 1/2"	5	BCVS-1-2160
	3000	4 1/2"	5	BCVS-1-3000
	5000	4 1/2"	5	BCVS-1-5000
2"	2160	6 3/8"	15	BCVS-2-2160
	3000	6 3/8"	15	BCVS-2-3000
	5000	6 3/8"	15	BCVS-2-5000



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

Line Check Valves

STAINLESS STEEL FLOW LINE CHECK VALVE



- 6,000 and 10,000 psig maximum working pressure
- 10-30 psig Cracking pressure
- 304 stainless steel body
- Inconel spring
- Available with:
 - Stainless steel or ceramic ball
 - Viton or teflon seat

SIZE	ORDER #
1/8	LCSS-1/8-6000-SSB-V
1/4	LCSS-1/4-6000-SSB-V, LCSS-1/4-6000-SSB-T
1/4	LCSS-1/4-6000-CEB-V, LCSS-1/4-6000-CEB-T
1/4	LCSS-1/4-10000-SSB-V, LCSS-1/4-10000-SSB-T
1/2	LCSS-1/2-6000-SSB-V

BRASS FLOW LINE CHECK VALVE



- 3000 psig maximum working pressure
- 10-30 psig cracking pressure
- 360 brass body
- Inconel spring
- Standard with 316 SS Ball, Viton Seal
- Ceramic Ball, Chrome Ball and Teflon seal also available

SIZE	ORDER #
1/4	LCB-1/4-3000-SSB-V, LCB-1/4-3000-T
1/4	LCB-1/4-3000-CEB-V, LCB-1/4-3000-CEB-T
1/4	LCB-1/4-3000-CHB-T
1/8	LCB-1/8-3000-SSB-V, LCB-1/8-3000-CEB-V, LCB-1/8-3000-CHB-V



2804 W. 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717
www.youngenergyproducts.com

THREADED BALL VALVES

DUCTILE IRON



VALVE SIZE	TYPE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	FP	1000	4"	4	BVD-1FP-1000
	FP	1500	4"	4	BVD-1FP-1500
	FP	2000	4"	4	BVD-1FP-2000
2"	FP	1000	6"	14	BVD-2FP-1000
	RP	1000	5 1/2"	11	BVD-2RP-1000
	FP	1500	6"	14	BVD-2FP-1500
	RP	1500	5 1/2"	11	BVD-2RP-1500
	FP	2000	6"	14	BVD-2FP-2000
	RP	2000	5 1/2"	11	BVD-2RP-2000
3"	FP	1000	8 1/2"	33	BVD-3FP-1000
	RP	1000	7 1/4"	15	BVD-3RP-1000
	FP	1500	8 1/2"	33	BVD-3FP-1500
	RP	1500	7 1/4"	15	BVD-3RP-1500
	FP	2000	8 1/2"	33	BVD-3FP-2000
	RP	2000	7 1/4"	15	BVD-3RP-2000

PERFORMANCE
PRODUCTS AS RELIABLE AS
THE PEOPLE

BEHIND THEM



2804 W 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717

www.youngenergyproducts.com

THREADED BALL VALVES

CARBON STEEL



VALVE SIZE	TYPE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1"	FP	3000	4"	5	BVS-1FP-3000
	FP	5000	4"	5	BVS-1FP-5000
2"	FP	3000	6"	14	BVS-2FP-3000
	RP	3000	5 1/2"	12	BVS-2RP-3000
	FP	5000	6"	14	BVS-2FP-5000
	RP	5000	5 1/2"	12	BVS-2RP-5000

THREADED BALL VALVES

BOLTED BODY

VALVE SIZE	TYPE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
3"	FP	3000	8 1/2"	34	BVS-3FP-3000-B
	RP	3000	7 1/4"	16	BVS-3RP-3000-B
	FP	5000	8 1/2"	34	BVS-3FP-5000-B
	RP	5000	7 1/4"	16	BVS-3RP-5000-B

VALVE SIZE	TYPE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
4"	FP	3000	9"	94	BVS-4FP-3000-B
	FP	5000	7 3/4"	94	BVS-4FP-5000-B



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

Tank Valves

DUCTILE IRON



VALVE SIZE	WORKING PRESSURE (PSI)	ORDER #
1/8"		LCB-1/8-3000
1/4"		
1/8"	6000	LCSS-1/8-6000
1/4"	6000	LCSS-1/4-6000
1/4"	10000	

GRADUATED DIAL COCK VALVE



VALVE SIZE	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
1/2"	2 1/2"	1.5	DC-1/2



2804 W 40th St
 Tulsa, OK 74107
 t. 800.346.6310
 f. 918.445.7717
www.youngenergyproducts.com

TANK VALVES

DUCTILE IRON



VALVE SIZE	WORKING PRESSURE (PSI)	END-TO-END LENGTH (IN)	WEIGHT (LBS)	ORDER #
2"	1000	5 1/2"	7	TVD-2-1000
	1000	5 1/2"	7	TVD-2-1000-ST
3"	1000	7 3/8"	14	TVD-3-1000
4"	1000	8 7/8"	33	TVD-4-1000-ST

***ST indicates ductile iron valve with carbon steel trim (carbon steel ball with Delrin seat)
All others come with stainless steel trim (stainless steel ball with Delrin seat)**



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717
www.youngenergyproducts.com

TERMS AND CONDITIONS

PRICING

All pricing and design standards are subject to change without notice. Customer orders are accepted with the understanding that prices in effect at the time of shipment will be invoiced to the customer and may, from time to time, vary from stated book prices. Prices quoted therein do not include federal, state or municipal sales or use, occupation or privilege taxes, based on or measured by sales; which tax or taxes will be added to prices where applicable.

DELIVERY

Shipment made from our factory, or from any company warehouse will be made to the best of our efforts within the time-frame indicated. We cannot be held responsible for delays in shipments caused by strikes, material conditions or delays beyond our control. All deliveries quoted for stock items are subject to prior sale.

CANCELLATION

Customer orders which have been accepted, scheduled, and ready for shipment, or any of the there, if canceled, are subject to reimbursement for costs incurred pursuant to the filling of the order.

FREIGHT

The buyer assumes responsibility for freight damages, delays, or loss of shipment. Freight will be prepaid in the continental U.S.A. on single destination orders in excess of \$1000 net invoice amount.

RETURNS

Any item of our manufacture may not be returned or exchanged unless written authorization is obtained from the Offices at Tulsa, OK. Any returned items will carry a minimum restocking charge of 15%, with freight paid to the factory by the customer.

TERMS OF PAYMENT

Net 30, with 1.5% interest per month charged on all past bills.



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717

www.youngenergyproducts.com

WARRANTY

YOUNG ENERGY PRODUCTS, LLC. products are warranted against failures by reason of defective workmanship or material within one year of the date of sale when the product is properly installed and operated, and subject to the following conditions and limitations. Our warranty is that we will repair or replace, at Young Energy Product's option, free of charge, any valve failing because of the stated defects within the time limit, providing that it is returned to our plant. The warranty does not extend to claims for labor expense, or other loss or damage occasioned by the failure. We do not warranty against deterioration by corrosion or any cause or failure other than a defect of material or workmanship in manufacture, nor do we guarantee a minimum length of service.

The warranty stated above is the sole warranty of the seller, any and every other warranty or guarantee of any kind, whether formally expressed or in any way implied, is nullified and excluded from the terms of sale. Purchasers are advised that the foregoing is the sole warranty offered by or acceptable to Young Energy Products, LLC., and that no other agent or employee of the company is authorized to contract for the sale of its product upon any other terms.



2804 W 40th St
Tulsa, OK 74107
t. 800.346.6310
f. 918.445.7717
www.youngenergyproducts.com

